

Andersons Golf Products

Turf Fertilizer 22-4-18

with MUTECH® Nitrogen & Iron

- Contains MUTECH nitrogen to provide uniform growth with extended nitrogen feeding
- Supplies iron to help prevent deficiencies

GUARANTEED ANALYSIS

Total Nitrogen (N)	22.00%
1.56% Ammoniacal Nitrogen	
3.05% Urea Nitrogen	
7.16% Water Insoluble Nitrogen	
10.23% Other Water Soluble Nitrogen*	
Available Phosphate (P ₂ O ₅)	4.00%
Soluble Potash (K ₂ O)	18.00%
Sulfur (S)	6.12%
6.12% Combined Sulfur (S)	
Iron (Fe)	1.00%

Plant nutrients derived from diammonium phosphate, potassium sulfate, methylene ureas and ferric oxide.

*10.23% slowly available nitrogen from methylene ureas.

F002091

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.regulatory-info-ap.com>

DIRECTIONS FOR USE

Apply only as directed during the growing season.

This product should be used when a soil test has been conducted, within the last 36 months, and the test indicates that the soil is deficient in plant available phosphorous or the intended use is for establishing grass or repairing damaged grass during the growing season in which the grass is established.

Application Rates:

LIGHT: 2.25 lbs/1,000 sq. ft.
NORMAL: 4.50 lbs/1,000 sq. ft.

FLORIDA APPLICATIONS:

We recommend that you follow the Florida Green Industries BMP's at http://www.flaes.org/pdf/BMP_Book_final.pdf

We recommend that you follow the Florida Golf Course BMP's at <http://www.flaes.org/pdf/gfbbmp07.pdf>

For all applications:

- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to prevent particle pick-up.

Cool Season Grasses:

- Apply at the NORMAL RATE in the spring and fall months.
- Apply at the LIGHT RATE in the summer months or when temperatures exceed 85°F.

Warm Season Grasses:

- Apply at the NORMAL RATE during the growing season.

Storage and Use:

Store in a clean, dry place.
Reseal opened bag by folding top down and securing.
Use only clean, dry spreaders.
Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.

Manufactured by:
The Andersons, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonsplantnutrient.com

MUTECH is a registered trademark of The Andersons, Inc.

Suggested Spreader Settings				
Suggested spreader settings are not intended to replace calibration. Please calibrate your spreader prior to applying product.				
50 lbs. feeds 22,200 sq. ft. (0.51 acre) with 0.50 lbs. N/1,000 sq. ft. at the LIGHT RATE				
50 lbs. feeds 11,100 sq. ft. (0.25 acre) with 1.00 lbs. N/1,000 sq. ft. at the NORMAL RATE				
SPREADER	GROUND SPEED	WIDTH OF COVERAGE	SPREADER SETTINGS	
			LIGHT RATE 2.25 lbs/1,000 sq. ft.	NORMAL RATE 4.50 lbs/1,000 sq. ft.
Andersons Model 2000 / AccuPro 2000 (cone 6); Andersons 2000 SR / SR-2000 (cone 6)	3 mph	10 feet	J 1/2	M 1/4
Scotts R-8A (cone 6)	3 mph	10 feet	J	L 1/2
Lesco 020093 (pattern 0.25)	3 mph	9 feet	D	E
Lesco 705698 (pattern 0.25)	3 mph	9 feet	10	12
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern III-B	4.5 mph	34 feet	4	5 1/4
Vicon (03 Series)	4.5 mph	25 feet	15	22

SGN 125
Net Wt. 50 Lbs. (22.68 kg)



AGC22715.40

G16*